High Humidity & Heat Resistant LED Lighting

- AC LED Driver-less Technology
- Intended for Use in High Ambient Temperature Environments



interlace for ose in ringir/timblent reinperature Environments							
	L1219A	COB	20W	220V			
	L1219B	COB	50W	110V, 220V			
	L1219C	COB	40W	110V, 220V			
			50W	110V, 220V			
	L1705A UL 1598 Luminaires CSA C22.2 No.250.0	COB	20W	120V, 277V			
	117050	COB	40W	120V, 277V			
	L1705G UL 1598 Luminaires CSA C22.2 No.250.0		50W	120V, 277V			
	L1319 2ft UL 1598 Luminaires CSA C22.2 No.250.0	SMD	40W	120V, 220V, 277V			
	L1319C 2ft UL 1598 Luminaires CSA C22.2 No.250.0	SMD	40W	120V, 220V, 277V			
	L1319C 4ft UL 1598 Luminaires CSA C22.2 No.250.0	SMD	40W	120V, 220V, 277V			

High Humidity & Heat Resistant LED Lighting

- AC LED Driver-less Technology
- Intended for Use in High Ambient Temperature Environments



L1105 UL 1598 Luminaires CSA C22,2 No.250.0	COB	40W	120V, 220V, 277V
L1102 UL 1598 Luminaires CSA C22.2 No.250.0	COB	60W	120V, 208V, 220V, 277V
L1512D UL 1598 Luminaires CSA C22.2 No.250.0	COB	140W	120V, 277V
		160W	120V, 277V

